# **Sensor Probes Overview**



# LABORATORY & EXPERIMENTS



#### **UV-Surface**

Universal radiometric UV sensor for calibration and reference measurements, cosine correction.
Often used with radiometer SXL55.



#### **UV-Cosine**

Waterproof dirt repellent UV sensor for outdoor measurement, cosine field of view. Also available as UVI sensor (ERYCA), M20x1.5 thread.



#### **UV-Air**

Axial measuring screw-in UV sensor very good EMC properties, M22x1.5 thread.



#### **TOCON-Probe**

Miniature UV sensor with o to 5 V voltage output, M12x1 thread.

# SPECIAL APPLICATIONS



### **UV-Arc**

Waterproof UV sensor for measurement of electric arcs between overhead contact wires and pantograph, complies with EN 50317,  $G_3/4$ " thread.



#### sglux ERYCA

high accuracy UV-Index sensor, measurement uncertainty is < 5%. The sensor complies with ISO 17166, M20x1.5 thread.



# UVI-Solo

like sglux ERYCA but configured as a ready-to-mount system (available for pole or railings assembly).



#### uvLink One

wireless UV sensor with a display unit for intensity and dose measurement.

# DUTY SENSORS MONITORING UV DISINFECTION OF AIR, SURFACES AND WATER



#### **UV-Sanitize**

UV sensor for monitoring of air and surface UV disinfection systems, configurable for monitoring of Hg low pressure lamps, excimer lamps or xenon flash lamps, M20x1.5 thread.



#### UV-Water-G3/4

UV sensor for operation in pressurized water (10 bar), for Hg medium and low pressure lamps.



#### **UV-Water-PTFE**

PTFE UV sensor for operation in pressurized water (10 bar), only for Hg low pressure lamps or LEDs, G1/4" thread.



#### UV-ÖNORM / UV-DVGW

UV sensor for DVGW(160°) and ÖNORM certified water purifiers, also available as UV-DVGW (40°). The sensors comply with ÖNORM M5873, DVGW W294(06), DIN19294



#### **UV-Radial**

Waterproof side looking UV sensor for monitoring of lamp bundles, for operation in a cladding tube or directly in water, M20x1.5 thread.



#### HIGH UV RADIATION



## **UV-Cure**

UV sensor for high irradiance (>100mW/cm²) for LED curing or cooled medium pressure lamps, M22x1.5 thread (temperature sensor available).



#### **UV-Cure HT**

Like UV-Cure but for temperatures up to 170°C, e.g. for uncooled medium pressure systems, M22x1.5 thread.